

AMENDMENT IN CHHATTISGARH SANCHAR PRATINIDHI KALYAN SAHAYTA NIYAM, 2019. DT. 27.05.2021

(üdT qt. ft. ü. 30-5-2001.' 27] (7) 2 11, 1943 3iR (3) (74) (1) a-TTTT R 3-1ZØ 21 2021 84T.y.ü. (2018), 553 qrqnt, a-VA 554 2 2021 27 2021 04-05/201 ?IIFT, fiqq- 2019, 29 2019 q. fiqq, 2019 :— 10 2.00 5.00 2.00 5.00 (3.7) (q) F. 5.00 2.50 7000/- 3 2 F. 1500 F. 2500/- (03 fig) F. 3500/- 50 2.50 2.50 23 2021 7-14/2013/12.—QGq 2/2010, 06-04-2010 21-09-2011 08-10- 2014 Ff fiq) fiqq, 2016 fiqq, 12 Differential Global Positioning System Pricise Boundary Pillar (1) 01. 02. 03. 04. 2 2021 (2) frfiiz, fifiüz, Rfiüz, fifiüz, 555 (3) DGPS Survey DGPS Survey 2. 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 03 10-11-2017 03 09-11-2020 t. 09-11-2020 03 t. fiuffia :— Each corner of the lease area shall have a boundary pillar (corner pillar). There shall be erected intermediate boundary pillars between the corner pillars in such a way that each pillar is visible from the adjacent pillar located on either side of it: The distance between two adjacent pillars shall not be more than fifty meters; The pillar shall be of square pytamid frustum shaped above the surface and cuboid shaped below the surface; Each pillars shall be of reinforced cement concrete; The corner pillar shall have a base of 0.3m x 0.3m and height of 1.30m of which 0.70m shall be above ground level and 0.60m below the ground; The intermediate pillars shall have a base of 0.25m x 0.25m and height of 1.0m of which 0.70m shall be above ground level and 0.30m below the ground; All pillars shall be painted in yellow colour and the top ten centimeters in red colour by enamel paint and shall be grouted with cement concrete. On all corner pillars, distance and being to the forward and backward pillars and latitude and longitude shall be marked. Each pillar shall have serial number in a clockwise direction and the number shall be engraved on the pillarss; The number of pillars shall be the numbers of the individual pillar upon the total number of pillars in the lease; 556 3. 12. 13. 14. 15. 16. 17. 18. 19. 20. 21. 2 2021 The tip of all the corner boundary pillars shall be a square of 15 centimeter on which a permanent circle of IO centimeter diameter shall be drawn by paint or engraved and the actual boundary point shall be intersection of two diameters drawn at 90 degrees. The lease boundary survey shall be accurate within such limits of error as the Control General, Indian Bureau of Mines may specify in this behalf; The loacation and number of the pillars shall also be shown in the surface and other plans main- tained by the lessee: and In case of forest area within the laese, the size and construction and colour of the boundary pillars shall be as per the norrnns specified by the Forest Department in this behalf. The Survey Agency shall be responsible for the accuracy of the data collected during Survey. Coordinates of boundary pillars shall be established in the world Geodetic System 1984 (WGS-84) Datum. fiä tITIT. 03 iü. 03 *TIT. 03 31 2021 AtRT-2018 03 2005 *ot) QQ-12 @-5400/-)